



**Note:**

1. When fixing the main body, please make use of all the screw holes on same mounting surface,
2. Don't exceed the depth of the threaded hole when tightening the bolt;
3. When the stroke is 50mm, if fixing the body from the top to the bottom, the fixing hole will be blocked by slider and only can be uses 4 screws to fix; as a result, suggest that fixing actuator body from the bottom to the top.

| Stroke | 50    | 100   | 150   | 200   | 250   | 300   | 350   | 400   | 450   | 500   | 550   | 600   | 650   | 700   | 750   | 800    |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|
| L      | 268.5 | 318.5 | 368.5 | 418.5 | 468.5 | 518.5 | 568.5 | 618.5 | 668.5 | 718.5 | 768.5 | 818.5 | 868.5 | 918.5 | 968.5 | 1018.5 |
| A      | 25    | 75    | 25    | 75    | 25    | 75    | 25    | 75    | 25    | 75    | 25    | 75    | 25    | 75    | 25    | 75     |
| M      | 1     | 1     | 2     | 2     | 3     | 3     | 4     | 4     | 5     | 5     | 6     | 6     | 7     | 7     | 8     | 8      |
| N      | 6     | 6     | 8     | 8     | 10    | 10    | 12    | 12    | 14    | 14    | 16    | 16    | 18    | 18    | 20    | 20     |
| P      | 25    | 75    | 125   | 175   | 225   | 275   | 325   | 375   | 425   | 475   | 525   | 575   | 625   | 675   | 725   | 775    |